



Cutting & Crimping Tools

Table of Contents

Product	Code	Page
Ratchet Cutter Cu/AL up to 300mm2	K3	<u>4</u>
Ratchet Cutter Cu/AL up to 500mm2	K4	<u>4</u>
Copper Aluminium Parrot Beak Ratchet Cutter C2	C2	<u>5</u>
Klein Ratchet Cutter	K325	<u>6</u>
Baudat K32	K32	<u>6</u>
Izumi Battery Ratchet Cable Cutter	RCS50E	<u>6</u>
Steel Wire Cable Cutters up to 750mm	KS62	<u>7</u>
Steel Wire Cable Cutters up to 1000mm	KS80	<u>7</u>
ACSR Ratchet Cable Cutter	S20	<u>8</u>
Copper & Aluminium Earth Tape Cutter	FS40	<u>8</u>
Hand Cable Cutters for Copper & Aluminium	CC	<u>9</u>
Hand Cable Cutters for Steel Rod and Steel Wire	HCC	<u>9</u>
Insulated Cable Cutters	ME	<u>9</u>
Izumi Hydraulic Cutters	S20-	<u>10</u>
Cembre Hydraulic Cutters	HT	<u>10</u>
Cembre Ht TC051Y	HT_TC051Y	<u>10</u>
Hydraulic Foot Pump	PO7000	<u>11</u>
Battery Operated Hydraulic Pump	B70M-P24-CH	<u>11</u>
Hydraulic Cutting Head	TC025	<u>12</u>
Hydraulic Cable Cutting Head up to 40mm OD	TC40	<u>12</u>
Hydraulic Cable Cutting Head up to 55mm OD	TC055	<u>12</u>
Hydraulic Cutting Head up to 120mm od	TC120	<u>13</u>
Open Head Hydraulic Cable Cutter	SDK85	<u>13</u>
Klauke 1000v Insulated Cable Cutter for Cu/Al	ES32ISM	<u>14</u>
Klauke 1000v Insulated ES20L ACSR Battery Cutting Tool	ES20IISM	<u>14</u>
Burndy MD6	MD6	<u>15</u>
Burndy Y35	CI-99	<u>15</u>
Klauke 1000v Insulated Mini Crimp Tool	EK425LISM	<u>16</u>
Klauke 12 Ton Battery powered crimping tool	EK120-30	<u>16</u>
Cembre W Die Crimp Tool	B54D-D6	<u>17</u>
Cembre W Die Crimp Tool B55KV	B55KV	<u>17</u>
Cembre B135-C-KV U Die Crimper	B135-C-KV	<u>17</u>
Milwaukee W Die Crimp Tool With SWA Cutting Head	M18	<u>18</u>
M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER	MHTCC	<u>19</u>
MILWAUKEE M18HCC75R-502C M18 FORCE LOGIC HYDRAULIC REMOTE	M18HCC75R-502C	<u>20</u>
Klauke 100 Tonne Crimp Head	PK1000	<u>21</u>
T 100 ton Crimp Head	t100	<u>21</u>
A & S Series 100 Ton Die Sets	65200615	<u>21</u>
Milwaukee W Die Crimp Tool With SWA Cutting Head	M18	<u>21</u>
Burndy W Die Sets	W	<u>22</u>

Product	Code	Page
Burndy U Die Sets	UDies	<u>22</u>
Izumi Crimp Die Sets	IDS	<u>22</u>
Cembre Die Sets	CT	<u>22</u>
Metal Die Box	MDB	<u>22</u>
Plastic Die Box	PDB	<u>22</u>

CU/AL RATCHET CABLE CUTTERS

Part No	Cross Section	Max OD	Length	Weight
K3	300mm ²	34mm od	255	1kg

Specially designed for cutting of multicore power cables.

- Movable blade can be release in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made In Germany



CU/AL RATCHET CABLE CUTTERS

Part No	Cross Section	Max OD	Length	Weight
K4	500mm ²	52mm	300	1.5kg

Specially designed for cutting of multicore power cables.

- Movable blade can be release in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made In Germany



CU/AL RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
C1	185mm ²	25mm	245mm

Parrot Beak specially designed for cutting single and multicore power cables.

- Movable blade – can be released in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut



CU/AL RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
C2	240mm ²	36mm	330

Parrot Beak specially designed for cutting single and multicore power cables.

- Movable blade – can be released in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut

- Cable cutter for copper and aluminium non-armoured cables up to 240mm².
- Ratchet design gives a large capacity tool that can fit in any toolbox.
- Precision ground blades for ease of operation and long service life.
- Safety lock and part cycle release functions.
- Soft feel insulated handles.



Part No: K325



Ratchet cable cutter with single handed operation
Open jaws for faster operation and greater access to restricted spaces

Cutting Capacity:
Copper and aluminium cables to 32mmØ
Copper cable to 250mm²
Aluminium cables to 320mm²

Blades releasable at any point during cutting

Part No: K32

This battery cable cutter specifically designed for cutting the toughest copper and aluminium cables in a limited amount of space.
Cuts are clean with a minimal amount of cable distortion.
Repetitive strain is eliminated.
Heavy duty cable cutter for non-ferrous cables up to 50 mm O.D

Part No: RCS50E



STEEL WIRE ARMOUR RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
KS62	750 mm	62	410

- Movable blade – can be released in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made in Germany



STEEL WIRE ARMOUR RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
KS80	1000mm	80mm	810mm

- Movable blade – can be released in all positions
- High quality tool steel ratchet mechanism
- No flattening of the cable – unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made in Germany



ACSR Cable Cutter

Part No	Cross Section	Max OD	Length	Weight
S50	350mm ²	50mm	230	1.1g

Specially designed for cutting of ACSR Cables.

- ACSR DIN 48 204 OD 24.5mm 7/2.67mm core
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made In Germany



Copper Earth Tape Cutter

Part No	Max Tape Thickness	Length	Weight
FS40	50mm x 6 mm	290	1.7kg

Specially designed for cutting of copper earth tape.

- Cuts Square
- Does not damage copper tape
- Easy to maintain
- Fast clean cut
- Made In Germany

Hand Cable Cutters for Copper and Aluminium

Part No	Cutting Capacity	Length
CC80	Cu /AL cables up to 80mm ²	320mm
CC250	Cu /AL cables up to 250mm ²	600mm
CC500	Cu /AL cables up to 500mm ²	800mm



Hand Cable Cutters for Steel rod and Steel Wire Rope

Code	Cutting Capacity	Length
HCC60S	Steel Rope 7mm , Wire Rope 5mm	310
HCC200S	Steel Rope 12mm , Wire Rope 9mm	580
HCC250S	Steel Rope 16mm , Wire Rope 11mm	600

Marvel Insulated cable cutters made in Japan Tested to 50000v

Part Code	Cutting Capacity	Length
ME 150S	Cu/AL 150mm ²	460mm
ME 250S	Cu/AL 250mm ²	615mm



Izumi Light weight portable hydraulic cutter

features:

Guillotine type cutting for less jamming than shear type cutting.

Part No	Wire Rope	ACSR	Soft Steel	Rebar	Guy Wire
S20	20mm	21mm	16mm	13mm	16mm
S24	24mm	24mm	20mm	20mm	20mm
S32	32mm	32mm	25mm	25mm	32mm



Cembre Hand operated hydraulic tool

The tool features a double speed action

The blades are manufactured from high strength steel,

The head can rotate through 180 degrees

HT series features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.



Part Code	Wire Rope	ACSR	Steel Rod	Cu/AL
HT-TC026	18mm	22.8mm	13mm	25mm
HT-TC041	18mm	39.2mm	11.5	40mm

Cembre Ht TC051Y

Hand operated hydraulic tool specifically designed to cut copper, aluminum, aluminum steel cables (ACSR)

having a max overall diameter of 50 mm.

The HT-TC051Y is provided with a two stage hydraulic system, which advances the blades quickly to the cable.



Foot operated double speed pump, developing a maximum pressure of 700 bar.

The pump is supplied with 3 m long high pressure flexible hose complete with female self-lock quick coupler.

Pressure can be withdrawn at any time during operation by depressing the release lever.

A solid shaped stand gives the pump stability during operation.



Part Number PO7000

Portable electro-hydraulic pump, operating at 24V dc by battery for independent use, developing 700 bar pressure;

integral socket for connection to an external 24 V dc supply.

Options:

It is also available insulated and operated by remote pneumatic hand controller and supplied with a non-conductive hose.



Part No: B70M-P24-CH

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.

Part No	ACSR	Wire Rope	Rod	Cu/AL
TC025	22.8mm	18mm	11mm	25mm



Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max



Part No	ACSR	Wire Rope	Rod	Cu/AL
TC40	39.2mm	18mm	20mm	40mm

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.

Part No	ACSR	Wire Rope	Rod	Cu/Al
TC055	50mm	14.3mm	22mm	55mm



TC120 **Hydraulic Cutting Head up to 120mm od**

Hydraulic cutting head specifically designed to cut copper, aluminium and telecommunications cables having a max overall diameter of 120 mm.

The head can easily be opened to cut running cables, and the handle allows the most comfortable positioning of the head onto the cable to be cut.

The head is complete with a quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.



SDK85 **Open Head Hydraulic Cable Cutter**

Cuts copper ,aluminium and ACSR up to 55mm² (depending on cable type)

Suitable for fine stranded cable and telecommunication cable

Exceptionally light and compact design

Safe working due to high ground stability by double stops

Characteristics

Open cutting head with quick coupling, under no pressure, rotates 360°

For connecting to hydraulic pumps with 700 bar operating pressure for best possible cutting results

Klaue 1000v Insulated Cable

Cutter for Cu/Al

Part No: ES32iSM

- Cuts multi-stranded copper and aluminium cables (ES 32-L
- Cuts fine and superfine stranded copper cables (ES 32 F-L)
- Slim cutting head - ideal when space is critical
- Open cutting head, rotatable
- One-button operating concept for controlling all tooling functions
- Ergonomic 2-component plastic housing with soft linings
- Balanced centre of gravity for easy handling
- LED for workplace illumination
- High-performance 18V Li-ion battery with high capacity



Klaue 1000v Insulated ES20L ACSR Battery Cutting Tool

Part No :ES20iISM

- For cutting Al/St conductors (ACSR) to DIN EN 50182
- solid Al/Cu cables to VDE 0295, Class 1 and laminated copper bus bars up to 20mm
- Extremely robust design and lightweight
- Slim cutting head - ideal when space is critical
- High-performance 18 V Li-Ion battery



The MD-6 Burndy Compression Tool .

- Available with either permanent "BG" and "D3" grooves.
- The "D3" groove accommodates the complete line of "W" die inserts.
- Easy tool adjustment with allen key.
- MD6-8 Option has "O" and "D3" grooves



Part No: Burndy MD6

The Y35 Burndy Hydraulic Crimping Tool has a C-shaped head

Rotates 180° for overhead line work and compression grounding applications.

Hydraulic Crimper features push-button die locks for Burndy "U" dies
12-tons of crimping force

Rapid ram advance automatic 10,000 PSI
blow-off pressure release valve for positive crimping



Part No: CI-99

EK425LISM Klauke 1000v Insulated Mini Crimp Tool

Klauke
New 1000v Insulated
Single Hand Battery Crimp Tool For W Dies

50KN Crimping Force

40mm Jaw Opening

Approx 140 Crimps Per Battery

3.0Kg

Supplied with 2 x 3ah Batteries and Vehicle



EK120-30 Klauke 12 Ton Battery powered crimping tool

U Die 12 Ton battery powered crimping tool has a large crimping range, for 10-400mm²
Up to 60% less crimping operations due to wide crimping

Kit Contents:

- EK 120/30L Tool
- Plastic Case
- Battery 18V / 3.0 Ah
- Quick Charger for 18V Li-Ion Batteries



Cembre W Die Crimp Tool

Cembre Single Handed Operation
Jaws rotate 180° for ease of operation in confined spaces.
Fitted with a maximum pressure valve.
Ni-MH battery; powerful, better environmental compatibility.
Two batteries and charger included.
Standard interchangeable crimping jaw: CDD6 with "D3" roove to accept all "W" style crimping dies + "BG" fixed groove.
CDD6-8 with "D3" roove to accept all "W" style crimping dies + "O" fixed groove Head Available
CMB1 Cutting Head for ACSR Available



Part No : B54D-D6

Cembre W Die Crimp Tool B55KV



14.4 V cordless hydraulic crimping tool
Lightweight and balanced for single hand operation.
The tool features a double speed action
The crimping head can rotate through 180° for ease of operation
The B 55, with adapter AU55-50, will accept all Cembre 50 kN dies; with adapter AU55-W it will accept "W" dies
Fitted with a maximum hydraulic pressure valve.
Complete with a battery condition display
Comes with 2 x Li-Lon Batteries and Vehicle charger

Part No : B55KV

Cembre B135-C-KV U Die Crimper

12Ton Battery Crimp tool for U dies
Double Speed advance
Head rotates 180 deg
weight 2.2kg
Supplied with 2 x 14.4v Li-Ion batteries
and vehicle charger



Part No : B135-C-KV

Milwaukee W Die Crimp Tool With SWA Cutting Head

- FORCE LOGIC™ ONE-KEY™ hydraulic utility crimping tool crimps connectors in less than 3 seconds with 53 kN of force
- Brushless POWERSTATE™ motor delivers up to 4x more motor life
- Best balanced tool and easiest control due to one-hand operation
- Compact in-line and slim jaw design with 350° rotatable head allows easy crimps, even in narrow spaces
- 2 in 1 solution: Crimping jaw can be exchanged for an ACSR, CU/ AL or armoured wire cable cutting jaw
- PFM™ (Predictive Force Monitoring): Automatically modifies output based on connector, ensuring optimal pressure every time and visualises with a green light
- Tool records & stores every crimp made. ONE-KEY™ enabled for professional report buildings via ONE-KEY™ app
- FORCE LOGIC™ long life reliability: Industry-leading 30,000 cycles between calibration inspections – The tool will continue to work after reaching 30,000 cycles
- Standard Equipment: W-Die jaw with fixed BG Crimping groove, SWA cutting jaw

Part Number :M18ONEHUTC-202B SWA Kit



M18™ FORCE LOGIC™ HYDRAULIC 109 KN CABLE CRIMPER

- Sealed electronics resist harsh environments with dirt, dust and moisture
- Lightest, most balanced tool with ergonomic grip design
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality
- Pre-crimp battery check automatically ensures enough charge to complete each crimp
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability
- -
- Red alignment marks on the tool jaws aid accuracy in crimp placement
- 42 mm jaw opening and 350° head rotation provides easy positioning and access, even for large connectors
- Crimps connectors with 109 kN of force
- PFM™ (Predictive Force Monitoring) with auto complete ensures full pressure and provides instant pressure verification with green indicator
- Allows to crimp connectors up to 400 mm²
- Universal die reception to fit most common U-Dies (C shaped dies) on the market
- The tool records & stores every crimp made for professional report building through both ONE-KEY™ app and ONE-KEY™ adaptor

Part Number: M18HCCT109/42-522C



MILWAUKEE M18HCC75R-502C M18 FORCE LOGIC HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER

Supplied with : 2x 5.0Ah li-ion batteries, fast charger & kitbox

- FORCE LOGIC™ hydraulic remote underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force.
- Wireless remote communicates with the tool via a mutually exclusive Bluetooth® connection, removing any physical connection to the tool and allowing Linemen to make remote cuts WIRELESSLY.
- Balanced design, handle and hang hook enable easiest set-up in vaults.
- Cuts aluminium & copper cables up to 75 mm.
- Green LED light on wireless remote gives positive indication that the tool is done cutting.
- Converts from Local to Remote cutting mode easily.
- Open jaw design provides easiest access in trenches.
- POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power.
- ONE-KEY™ technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- REDLINK™ individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- REDLITHIUM™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

3 YEAR EXTENDED WARRANTY - when you register your tool online @ warranty.milwaukeetool.eu

- One-Key : Yes

Part Number:
M18HCC75R-502C





Klauke 100 Tonne Crimp Head

- Single-acting crimping head for connecting to hydraulic pumps with 700 bar operating pressure
- Compact, simple design
- Extremely high crimping force
- For interchangeable dies (outer: to IZUMI standard EP-100W,
- Nickel-plated version
- Quick coupling

Part No
PK1000

Crimp Range
1600mm²


weight
27kg

T 100 ton Crimp Head

- Working Pressure 10,000 psi (700 bar)
- 100 tons Crimping Force
- Built in safety relief valve prevents accidental damage
- Vast range of dies available and accepts shell type 'C' Dies
- Easy, one handed die removal
- One-piece design
- Coupling/hose protective guard
- Optional Cycle Counter
- Comfy-grip coated handles
- Different quick release coupling options available
- Dimensions Ø192mm x 314mm
- Weight 26kg



Milwaukee W Die Crimp Tool



CONDUCTOR ACSR		ALCAN Die No's			
CODE	DIA mm	ALUM.	A/F mm	STEEL.	A/F mm
WOLF	18.13	A-8	28.2	S-8	12.7
HORSE	13.95	A-9	32.3	S-9	15.2
PANTHER	21.00	A-9	32.3	S-9	15.2
* KEZIAH	19.53	A-9	32.3	S-9	15.2
BEAR	23.45	A-9	32.3	S-10	16.1
LYNX	19.53	A-9	32.3	S-10	16.1
GOAT	25.97	A-10	36.2	S-10	16.1
ZEBRA	28.62	A-11	40.2	S-10	16.1
DINOSAUR	35.56	A-13	49.7	S-12	20.2
CENTIPEDE	26.49	A-10	36.2	N/A	N/A
BULL	38.00	A-13	49.7	N/A	N/A


Burndy W Die Sets

W162	W162	W163	W164
W166	W203	W204	W239
W243	W245	W247	W249
W373	W658	W659	W698
W699	WGB	WC	WE
WO	W120BGE2T	W140BGE2T	W173BGE2T
W215BGE2T	W28K Cutting Die		



U161	U162	U163	U614
U165	U166	U167	U168
U169	U170	U203	U204
U209	U243	U247	U249
U305	U315	U317	U373
U642	U654	U655	U658
U659	U698	U699	U708
U756	U790	U878	UBG
UC	UD3	UE	UF
UH	UN	UO	U173BGE5T
U215BGE5T			

Izumi Die Sets



Cembre CT & HT Die Sets



**Metal Die Box
For W and U
Dies**



**Plastic Die Box
for W and U
Dies**