

Cutting & Crimping Tools

Table of Contents

Product	Code	Page
Ratchet Cutter Cu/AL up to 300mm2	K3	<u>4</u>
Ratchet Cutter Cu/AL up to 500mm2	K4	<u>4</u>
Copper Aluminium Parrot Beak Ratchet Cutter C2	C2	<u>5</u>
Klein Ratchet Cutter	K325	<u>6</u>
Baudat K32	K32	<u>6</u>
Izumi Battery Ratchet Cable Cutter	RCS50E	<u>6</u>
Klien Battery Cable Cutter	BAT20GD14H	<u>8</u>
Steel Wire Cable Cutters up to 750mm	KS62	<u>9</u>
Steel Wire Cable Cutters up to 1000mm	KS80	<u>9</u>
ACSR Ratchet Cable Cutter	S20	<u>10</u>
Copper & Aluminium Earth Tape Cutter	FS40	<u>10</u>
Hand Cable Cutters for Copper & Aluminium	CC	<u>11</u>
Hand Cable Cutters for Steel Rod and Steel Wire	HCC	<u>11</u>
Insulated Cable Cutters	ME	<u>11</u>
Izumi Hydraulic Cutters	S20-	<u>12</u>
Cembre Hydraulic Cutters	HT	<u>12</u>
Cembre Ht TC051Y	HT_TC051Y	<u>12</u>
Hydraulic Foot Pump	PO7000	<u>13</u>
Battery Operated Hydraulic Pump	B70M-P24-CH	<u>13</u>
Hydraulic Cutting Head	TC025	<u>14</u>
Hydraulic Cable Cutting Head up to 40mm OD	TC40	<u>14</u>
Hydraulic Cable Cutting Head up to 55mm OD	TC055	<u>14</u>
Hydraulic Cutting Head up to 120mm od	TC120	<u>15</u>
Open Head Hydraulic Cable Cutter	SDK85	<u>15</u>
Klauke 1000v Insulated Cable Cutter for Cu/Al	ES32iSM	<u>16</u>
Klauke 1000v Insulated ES20L ACSR Battery Cutting Tool	ES20IISM	<u>16</u>
Burndy MD6	MD6	<u>17</u>
Burndy Y35	CI-99	<u>17</u>
Klauke 1000v Insulated Mini Crimp Tool	EK425LISM	<u>18</u>
Klauke 12 Ton Battery powered crimping tool	EK120-30	<u>18</u>
Cembre W Die Crimp Tool	B54D-D6	<u>19</u>
Cembre W Die Crimp Tool B55KV	B55KV	<u>19</u>
Cembre B135-C-KV U Die Crimper	B135-C-KV	<u>19</u>
Burndy W Die Crimp Tool	PATMD6	<u>20</u>
Burndy 12 Ton U Die Tool	PAT750LI	<u>20</u>
Burndy Die Less Crimp Tool	PAT-4PC834-LI	<u>20</u>
Klauke 100 Tonne Crimp Head	PK1000	<u>21</u>
T 100 ton Crimp Head	t100	<u>21</u>
A & S Series 100 Ton Die Sets	65200615	<u>21</u>
Burndy 12 Ton U Die Tool	PAT750LI	<u>21</u>

Product	Code	Page
Burndy W Die Sets	W	<u>22</u>
Burndy U Die Sets	UDies	<u>22</u>
Izumi Crimp Die Sets	IDS	<u>22</u>
Cembre Die Sets	CT	<u>22</u>
Metal Die Box	MDB	<u>22</u>
Plastic Die Box	PDB	<u>22</u>

CU/AL RATCHET CABLE CUTTERS

Part No Cross Section Max OD Length Weight

K3 300mm2 34mm od 255 1kg

Specially designed for cutting of multicore power cables.

- •Movable blade can be release in all positions
- High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- •Cuts fine stranded copper cables
- Easy to maintain
- •Fast clean cut
- •Made In Germany





CU/AL RATCHET CABLE CUTTERS

Part No Cross Section Max OD Length Weight
K4 500mm2 52mm 300 1.5kg

Specially designed for cutting of multicore power cables.

- •Movable blade can be release in all positions
- •High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- •Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut
- Made In Germany

Page 4 www.ukusp.co.uk sales@ukusp.co.uk Tel:01782537200

CU/AL RATCHET CABLE CORE CUTTERS

Part No Cross Section Max OD Length

C1 185mm2 25mm 245mm

Parrot Beak specially designed for cutting single and multicore power cables.

- •Movable blade can be released in all positions
- •High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- Cuts fine stranded copper cables
- Easy to maintain
- Fast clean cut



CU/AL RATCHET CABLE CORE CUTTERS

Part No Cross Section Max OD Length

C2 240mm2 36mm 330

Parrot Beak specially designed for cutting single and multicore power cables.

- •Movable blade can be released in all positions
- •High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- Cuts fine stranded copper cables
- •Easy to maintain
- •Fast clean cut

- Cable cutter for copper and aluminium non-armoured cables up to 240mm².
- Ratchet design gives a large capacity tool that can fit in any toolbox.
- Precision ground blades for ease of operation and long service life.
- Safety lock and part cycle release functions.
- Soft feel insulated handles.

Part No: K325





Ratchet cable cutter with single handed operation Open jaws for faster operation and greater access to restricted spaces

Cutting Capacity:
Copper and aluminium cables to 32mmØ
Copper cable to 250mm²
Aluminium cables to 320mm²

Blades releasable at any point during cutting

Part No: K32

This battery cable cutter specifically designed for cutting the toughest copper and aluminium cables in a limited amount of space.

Cuts are clean with a minimal amount of cable distortion.

Repetitive strain is eliminated.

Heavy duty cable cutter for non-ferrous cables up to 50 mm O.D

Part No: RCS50E







STEEL WIRE ARMOUR RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
KS62	750 mm	62	410

- •Movable blade can be released in all positions
- •High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- •Cuts fine stranded copper cables
- •Easy to maintain
- •Fast clean cut
- •Made in Germany





STEEL WIRE ARMOUR RATCHET CABLE CORE CUTTERS

Part No	Cross Section	Max OD	Length
KS80	1000mm	80mm	810mm

- •Movable blade can be released in all positions
- •High quality tool steel ratchet mechanism
- •No flattening of the cable unique blade profile
- •Cuts fine stranded copper cables
- •Easy to maintain
- •Fast clean cut
- Made in Germany

Page 9 www.ukusp.co.uk sales@ukusp.co.uk Tel:01782537200

ACSR Cable Cutter

Part No Cross Section Max OD Length Weight

S50 350mm2 50mm 230 1.1g

Specially designed for cutting of ACSR Cables.

- •ACSR DIN 48 204 OD 24.5mm 7/2.67mm core
- •Cuts fine stranded copper cables
- •Easy to maintain
- Fast clean cut
- Made In Germany



Copper Earth Tape Cutter

Part No Max Tape Thickness Length Weight

FS40 50mm x 6 mm 290 1.7kg

Specially designed for cutting of copper earth tape.

- •Cuts Square
- •Does not damage copper tape
- Easy to maintain
- Fast clean cut
- Made In Germany



Page 10 www.ukusp.co.uk sales@ukusp.co.uk Tel:01782537200

Hand Cable Cutters for Copper and Aluminium

Part No	Cutting Capacity	Length
CC80	Cu /AL cables up to 80mm2	320mm
CC250	Cu /AL cables up to 250mm2	600mm
CC500	Cu /AL cables up to 500mm2	800mm





Hand Cable Cutters for Steel rod and Steel Wire Rope

Code	Cutting Capacity	Length
HCC60S	Steel Rope 7mm , Wire Rope 5mm	310
HCC200S	Steel Rope 12mm , Wire Rope 9mm	580
HCC250S	Steel Rope 16mm , Wire Rope 11mm	600

Marvel Insulated cable cutters made in Japan Tested to 50000v

Part CodeCutting CapacityLengthME 150SCu/AL 150mm2460mmME 250SCu/AL 250mm2615mm



Izumi Light weight portable hydraulic cutter features:

Guillotine type cutting for less jamming than shear type cutting.

Part No	Wire Rope	ACSR	Soft Steel	Rebar	Guy Wire
S20	20mm	21mm	16mm	13mm	16mm
S24	24mm	24mm	20mm	20mm	20mm
S32	32mm	32mm	25mm	25mm	32mm





Cembre Hand operated hydraulic tool
The tool features a double speed action
The blades are manufactured from high strength
steel,

The head can rotate through 180 degrees
HT series features an automatic safety valve to
bypass oil when reaching maximum pressure; a
pressure release device can also be operated at any
stage of operation.

Part Code	Wire Rope	ACSR	Steel Rod	Cu/AL
HT-TC026	18mm	22.8mm	13mm	25mm
HT-TC041	18mm	39.2mm	11.5	40mm

Cembre Ht TC051Y

Hand operated hydraulic tool specifically designed to cut copper, aluminum, aluminum steel cables (ACSR)

having a max overall diameter of 50 mm.

The HT-TC051Y is provided with a two stage hydraulic system, which advances the blades quickly to the cable.



Page 12 www.ukusp.co.uk sales@ukusp.co.uk Tel:01782537200

Foot operated double speed pump, developing a maximum pressure of 700 bar.

The pump is supplied with 3 m long high pressure flexible hose complete with female self-lock quick coupler.

Pressure can be withdrawn at any time during operation by depressing the release lever.

A solid shaped stand gives the pump stability during operation.



Part Number PO7000



Portable electro-hydraulic pump, operating at 24V dc by battery for independent use, developing 700 bar pressure;

integral socket for connection to an external 24 V dc supply.

Options:

It is also available insulated and operated by remote pneumatic hand controller and supplied with an non-conductive hose.

Part No: B70M-P24-CH

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.

Part No ACSR Wire Rope Rod Cu/AL TC025 22.8mm 18mm 11mm 25mm





Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max

Part No ACSR Wire Ro

Wire Rope Rod 18mm 20mm Cu/AL 40mm

Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.

Part No TC055 ACSR 50mm Wire Rope Rod 14.3mm 22mm Cu/Al 55mm



TC120 Hydraulic Cutting Head up to 120mm od

Hydraulic cutting head specifically designed to cut copper, aluminium and telecommunications cables having a max overall diameter of 120 mm.

The head can easily be opened to cut running cables, and the handle allows the most comfortable positioning of the head onto the cable to be cut.

The head is complete with a quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max.





SDK85 Open Head Hydraulic Cable Cutter

Cuts copper ,aluminium and ACSR up to 55mm2 (depending on cable type)
Suitable for fine stranded cable and telecommunication cable
Exceptionally light and compact design
Safe working due to high ground stability by double stops

Characteristics

Open cutting head with quick coupling, under no pressure, rotates 360°

For connecting to hydraulic pumps with 700 bar operating pressure for best possible cutting results

Klauke 1000v Insulated Cable Cutter for Cu/Al

Part No: ES32iSM

- Cuts multi-stranded copper and aluminium cables (ES 32-L
- Cuts fine and superfine stranded copper cables (ES 32 F-L)
- Slim cutting head ideal when space is critical
- Open cutting head, rotatable
- One-button operating concept for controlling all tooling functions
- Ergonomic 2-component plastic housing with soft linings
- · Balanced centre of gravity for easy handling
- LED for workplace illumination
- High-performance 18V Li-ion battery with high capacity



Klauke 1000v Insulated ES20L ACSR Battery Cutting Tool

Part No :ES20IISM



 solid Al/Cu cables to VDE 0295, Class 1 and laminated copper bus bars up to 20mm

Extremely robust design and lightweight

Slim cutting head - ideal when space is critical

High-performance 18 V Li-Ion battery



The MD-6 Burndy Compression Tool.

- Available with either permanent "BG" and "D3" grooves.
- The "D3" groove accommodates the complete line of "W" die inserts.
- Easy tool adjustment with allen key.
- MD6-8 Option has "O" and "D3" grooves



Part No: Burndy MD6



The Y35 Burndy Hydraulic Crimping Tool has a C-shaped head

Rotates 180° for overhead line work and compression grounding applications.

Hydraulic Crimper features push-button die locks for Burndy "U" dies 12-tons of crimping force

Rapid ram advance automatic 10,000 PSI blow-off pressure release valve for positive crimping

Part No:CI-99

Page 17 www.ukusp.co.uk sales@ukusp.co.uk Tel:01782537200

EK425LISM Klauke 1000v Insulated Mini Crimp Tool

Klauke New 1000v Insulated Single Hand Battery Crimp Tool For W Dies

50KN Crimping Force

40mm Jaw Opening

Approx 140 Crimps Per Battery

3.0Kg

Supplied with 2 x 3ah Batteries and Vehicle





EK120-30 Klauke 12 Ton Battery powered crimping tool

U Die 12 Ton battery powered crimping tool has a large crimping range, for 10-400mm² Up to 60% less crimping operations due to wide crimping

Kit Contents:

- EK 120/30L Tool
- Plastic Case
- Battery 18V / 3.0 Ah
- Quick Charger for 18V Li-Ion Batteries

Cembre W Die Crimp Tool

CembreSingle Handed Operation Jaws rotate 180° for ease of operation in confined spaces.

Fitted with a maximum pressure valve.

Ni-MH battery; powerful, better environmental compatibility.

Two batteries and charger included.

Standard interchangeable crimping jaw: CDD6 with "D3" roove to accept all "W" style crimping dies + "BG" fixed groove.

CDD6-8 with "D3" roove to accept all "W" style crimping dies + "O" fixed groove Head Available CMB1 Cutting Head for ACSR Available

Part No: B54D-D6



Cembre W Die Crimp Tool B55KV

14.4 V cordless hydraulic crimping tool Lightweight and balanced for single hand operation. The tool features a double speed action The crimping head can rotate through 180° for ease of operation

The B 55, with adapter AU55-50, will accept all Cembre 50 kN dies; with adapter AU55-W it will accept "W" dies Fitted with a maximum hydraulic pressure valve. Complete with a battery condition display Comes with 2 x Li-Lon Batteries and Vehicle charger

Part No: B55KV

Cembre B135-C-KV U Die Crimper

12Ton Battery Crimp tool for U dies Double Speed advance Head rotates 180 deg weight 2.2kg Supplied with 2 x 14.4v Li-Ion batteries and vehicle charger

Part No: B135-C-KV





Burndy W Die Crimp Tool

The BURNDY® PATRIOT® High Performance tool 80% faster than previous models

- Refined hydraulic system for ultra performance, speed and reliability.
- Advance design high speed pump completes a crimp in approximately 2 seconds.
- True, one-handed operation for advance, retract, and hold.
- Pressure "pop-off" valve indicates completion of crimp.
- Ram holds position when trigger is released to allow the operator to check alignment prior to crimping.

Burndy 12 Ton U Die Tool

The BURNDY[®] PATRIOT[®] Lithium-Ion tools incorporate the latest engineering technology with a patented high speed hydraulic pump

- Tool Weight: 15.7 lbs. (7.12 kg) With Battery
- State of the art crimping head design, 355° head rotation lets user get into tight areas easier
- Allows use of standard BURNDY ® dies already in use
- PAT750C-LI with rubber covered head is available
- 5-year limited warranty on tool
- Lifetime warranty on INFINITY DRIVE ®
- 1-year warranty on batteries and charger
- Recharge Time: 30 minutes





Burndy Die Less Crimp Tool

The BURNDY[®] PATRIOT[®] Lithium-Ion tools incorporate the latest engineering technology with a patented high speed hydraulic pump

- Output Force: 6 tons (5.4 metric tons)
- Die less system eliminates the need to purchase and maintain dies
- Die less system allows connectors and splices to become range taking
- Tool Weight: 13 lbs. (5.9 kg) with Battery



Klauke 100 Tonne Crimp Head

- Single-acting crimping head for connecting to hydraulic pumps with 700 bar operating pressure
- Compact, simple design
- · Extremely high crimping force
- For interchangeable dies (outer: to IZUMI standard EP-100W,
- Nickel-plated version
- Quick coupling

Part No Crimp Range weight

T 100 ton Crimp Head

- Working Pressure 10,000 psi (700 bar)
- 100 tons Crimping Force
- Built in safety relief valve prevents accidental damage
- Vast range of dies available and accepts shell type 'C' Dies
- Easy, one handed die removal
- One-piece design
- Coupling/hose protective guard
- Optional Cycle Counter
- Comfy-grip coated handles
- Different quick release coupling options available
- Dimensions Ø192mm x 314mm
- Weight 26kg

Burndy 12 Ton U Die Tool





CONDUCTOR ACSR		ALCAN Die No's			
CODE	DIA mm	ALUM.	A/F mm	STEEL.	A/F mm
WOLF	18.13	A-8	28.2	S-8	12.7
HORSE	13.95	A-9	32.3	S-9	15.2
PANTH ER	21.00	A-9	32.3	S-9	15.2
* KEZIAH	19.53	A-9	32.3	S-9	15.2
BEAR	23.45	A-9	32.3	S-10	16.1
LYNX	19.53	A-9	32.3	S-10	16.1
GOAT	25.97	A-10	36.2	S-10	16.1
ZEBRA	28.62	A-11	40.2	S-10	16.1
DINOS AUR	35.56	A-13	49.7	S-12	20.2
CENTIP EDE	26.49	A-10	36.2	N/A	N/A
BULL	38.00	A-13	49.7	N/A	N/A

Burndy W Die Sets

W162	W162	W163	W164
W166	W203	W204	W239
W243	W245	W247	W249
W373	W658	W659	W698
W699	WGB	WC	WE
WO	W120BGE2T	W140BGE2T	W173BGE2T



W215BGE2T W28K Cutting

Die



U161	U162	U163	U614
U165	U166	U167	U168
U169	U170	U203	U204
U209	U243	U247	U249
U305	U315	U317	U373
U642	U654	U655	U658
U659	U698	U699	U708
U756	U790	U878	UBG
UC	UD3	UE	UF
UH	UN	UO	U173BGE5T
U215BGE5T			

Izumi Die Sets



Cembre CT & HT Die Sets





Metal Die Box For W and U Dies



Plastic Die Box for W and U Dies