





**XL BRANDS - GOLD  
STIX PREMIUM MULTI-  
PURPOSE ADHESIVE 4  
GALLON**



**EAST BAY - 391 BRIG  
PROFESSIONAL MULTI-  
PURPOSE ADHESIVE 4  
GALLON**

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

**Features:**

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

**Coverage and Trowel Options:**

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

**Features:**

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

**Coverage and Trowel Options:**

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

**Features:**

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

**Features:**

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## SCHÖNOX - SHP SPECIAL ACRYLIC PRIMER



## BOSTIK - D-25 DITRA- SET THIN SET & MEDIUM BED MORTAR 50 LB

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## SCHÖNOX - SL CEMENT BASED RAPID DRYING, SMOOTHING & FINISHING COMPOUND 10 LB



## ROBERTS - 3000 MULTI PURPOSE FLOORING ADHESIVE

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



**BOSTIK - BOSTIK'S  
BEST URETHANE  
WOOD ADHESIVE &  
MOISTURE VAPOR  
CONTROL 4 GALLON**



**PALMETTO ROAD -  
URETHANE WOOD  
ADHESIVE 4 GALLON**

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

**Features:**

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

**Coverage and Trowel Options:**

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

**Features:**

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

**Coverage and Trowel Options:**

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

**Features:**

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

**Features:**

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## TEGO - PRO DOUBLE STICK TAPE - 165' ROLL



## ROBERTS - 7200HP HIGH PERFORMANCE BOND BASE ADHESIVE

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## TEGO - MASKING TAPE 2" X 180'



## TEGO - DUCT TAPE 2" X 180'

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## TEGO - PRO FLAT BACK TAPE 2" X 180'



## EAST BAY - 491 SCHOONER PREMIUM MULTI PURPOSE ADHESIVE 4 GALLON

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.


**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25





## TEGO - PRO BLUE MASKING TAPE 2" X 180'



## PALMETTO ROAD - MS POLYMER WOOD ADHESIVE 3 GALLON

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30618591  
East Bay Supply SKU: BSKBOSTIKBEST4G

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

Supplier SKU: 30850787  
East Bay Supply SKU: BSKD25

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25



## SCHÖNOX - EPA RAPID TWO-PART RAPID CURING EPOXY BASED MOISTURE MITIGATION SYSTEM

*Supplier SKU: 30618591*  
*East Bay Supply SKU: BSKBOSTIKBEST4G*

Bostik's BEST is a high-performance urethane adhesive and moisture control membrane that provides a tough, flexible bond to a variety of surfaces. Bostik's BEST high tacking formula exhibits exceptional green grab immediately after troweling, making installation easier and more secure.

### Features:

- Low VOCs
- Does not contain water
- Moisture vapor protection
- Bostik's Blockade antimicrobial protection

**Floor Types:** Solid & engineered wood, bamboo, cork, parquet, plywood, and ceramic tile, marble & stone inlays.

**Open/Working Time:** 180 minutes

### Coverage and Trowel Options:

Adhesive & Moisture Membrane Installation Method:

- Engineered wood up to 5/8" thick: 1/4"x1/4" V notch OR 1/4"x1/4"x1/4" square notch, 30-35 sq ft per gallon
- Engineered wood greater than 5/8" thick: 1/2"x15/32" V notch OR 1/4"x3/8"x1/4" square notch, 20 sq ft per gallon

Adhesive Only Installation Method:

- Engineered wood up to 1/2" thick: 3/16"x5/32" V notch, 50 sq ft per gallon
- Parquet up to 1/2" thick, or cork underlayment: 1/8"x1/8"x1/8" square notch, 80 sq ft per gallon
- Engineered wood greater than 1/2" thick, solid wood or bamboo flooring up to 1/2" thick, and parquet up to 3/4" thick: 1/4"x1/4"x1/4" square notch, 40 sq ft per gallon
- Solid wood or bamboo greater than 1/2" thick, or plywood: 1/4"x1/4"x1/4" square notch, 35 sq ft per gallon

**Shelf Life:** 12 months from date of manufacturing

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKBOSTIKBEST4G

*Supplier SKU: 30850787*  
*East Bay Supply SKU: BSKD25*

Bostik's D-25 DITRA-SET Thin Set & Medium Bed Mortar provides outstanding workability, excellent durability, significant leveling characteristics, and superior bond strengths in interior and exterior applications. Bostik Ditra-Set is composed of select proprietary chemicals, carefully graded aggregates, and purified cements.

### Features:

- For interior and exterior installations in conjunction with Schluter®-DITRA and Schluter®-KERDI uncoupling and waterproofing membranes
- Exceeds ANSI A118.1 when mixed with water
- Recommended for use with porcelain and large format tiles over uncoupling membranes

**Coverage:** 40-60 square foot per unit using 1/4"x3/8" square notch trowel.

**Shelf Life:** 1 year from date of manufacture in unopened bag.

[Technical Data Sheet](#)

SKU	Size
-----	------

BSKD25

*East Bay Supply SKU: EBSER2914G*